Specifications

Eaton MTL7710-

Eaton Crouse-Hinds series MTL7700 Zener barrier, For 4/6V systems, 10 Vdc, 200mA, Polycarbonate, DIN rail mount, - polarity

General specifications	
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
CATALOG NUMBER	MTL7710-
EAN	3066227675748
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	12.6 mm
PRODUCT WEIGHT	140 g

Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	IECEx/ATEX NEC/CEC IEC
NEC HAZARDOUS RATING	Class I, Zone 2 Class I, Division 2
IECEX/ATEX HAZARDOUS RATING	Zone 2 Zone 0
INGRESS PROTECTION (IP) RATINGS	IP20

Product specifications

TYPICAL APPLICATION	4/6V systems
RATED SUPPLY VOLTAGE DC	10 Vdc
TYPE OF POWER SUPPLY	DC
SWITCHING CURRENT	200mA
MATERIAL	Polycarbonate
MOUNTING METHOD	DIN rail
MINIMUM OPERATING TEMPERATURE	-20 °C
MAXIMUM OPERATING TEMPERATURE	60 °C

Resources

INSTALLATION INSTRUCTIONS	MTL7700 Range Instruction Manual MTL7700 ATEX Safety Instructions
TECHNICAL SERVICE BULLETINS	MTL7700 Range datasheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.