Specifications



Eaton MTL7778AC

Eaton Crouse-Hinds series MTL7700 Zener barrier, 28 Vdc, 47mA, Polycarbonate, DIN rail mount

General specifications	
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
CATALOG NUMBER	MTL7778AC
EAN	3066227675717
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	12.6 mm
PRODUCT WEIGHT	140 g

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	IECEx/ATEX NEC/CEC IEC
NEC HAZARDOUS RATING	Class I, Zone 2 Class I, Division 2
IECEX/ATEX HAZARDOUS RATING	Zone 0 Zone 2
INGRESS PROTECTION (IP) RATINGS	IP20

Product specifications

RATED SUPPLY VOLTAGE DC	28 Vdc
TYPE OF POWER SUPPLY	DC
SWITCHING CURRENT	47mA
MATERIAL	Polycarbonate
MOUNTING METHOD	DIN rail
MINIMUM OPERATING TEMPERATURE	-20 °C
MAXIMUM OPERATING TEMPERATURE	60 °C

Resources

INSTALLATION INSTRUCTIONS	MTL7700 ATEX Safety Instructions MTL7700 Range Instruction Manual
TECHNICAL SERVICE BULLETINS	MTL7700 Range datasheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2026 Eaton. All Rights Reserved.