

XB9 5 joule xenon beacon range

Ex d, weatherproof



Overview

These compact and lightweight beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The beacon housing, including the flamepaths, is manufactured completely from a UV stable glass reinforced polyester which is ideally suited for use offshore and onshore.

Stainless steel screws and mounting bracket are incorporated ensuring a totally corrosion free unit.

Units can be painted to customer specification and supplied with identification labels.

Features

- Zone 1 and Zone 2 use
- Ex d IIC T5/T6
- ATEX approved, Ex II 2G
- IECEx certified Gb
- IP66 and IP67
- Certified temperature -55°C to +55°C

- Corrosion Free GRP
- Various lens colours
- Lens guard fitted as standard
- Optional gland plus cable tail
- Stainless steel mounting bracket & screws
- Replaceable tube



Certifications

ATEX Ex d	Cert. no. Baseefa BAS00ATEX2031 Certified to: EN60079-0, EN60079-1 Ex II 2G, Ex d IIC T5/T6 Gb
IECEX Ex d	Cert. no. IECEX BAS 10.0113 Certified to: IEC60079-0, IEC60079-1 Ex d IIC T5/T6 Gb

Specifications

Material	Body & cover: glass reinforced polyester (GRP) Lens: glass Cover screws & bracket: stainless steel 316
Finish	Natural black or painted to customer specification
Weight	1.6kg
Certified temp	-55°C to +40°C (T6). -55°C to +55°C (T5)
Ingress protection	IP66 & IP67
Fire retardancy	GRP is fire retardant to IEC 60695-11-10
Terminals	3 x 2.5mm ²
Mounting	Wall mounted via bracket
Entries	1 x M20 or PG 13.5
Optional	1 x 3m cable tail and gland
Tube life	>1x10 ⁶ flashes

Electrical ratings:

	d.c				a.c.	
Voltage	12	24	48	60	110	240/254
Tube energy (J)	5	5	5	5	5	5
Current (A)	0.65	0.35	0.18	0.13	0.08	0.06/0.057
Effective intensity (Cd)	29	29	29	29	29	29
Peak intensity (Cd)	22213	22213	22213	22213	22213	22213
Power consumption (W)	8	9	9	8	9	15

Note: The above figures (Cd) are for a clear lens @ 1Hz flash rate

Multiplying factor for coloured lenses:

Red	Blue	Amber	Green	Yellow
0.15	0.12	0.51	0.49	0.86

The photometric data has been verified by BSI. A report is available if required

Ordering requirements

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box

Model	Certification	Voltage	Flashrate	Lens	Lens guard	Tag/duty	Entries/cable tail	Finish	
XB9									
Certification Uncertified W ATEX D IECEX J		Flash rate 60 / min 06 Other flash rates available on request, please specify		Guard Yes Y		Entries 1 x M20 1B 1 x PG 13.5 1P Cable & tail 3m cable CB		Finish Natural black N Red R Blue B Yellow Y Grey G White W Special S*	
		Voltage 12Vdc 012 24Vdc 024 48Vdc 048 60Vdc 060 110Vac 110 240Vac 240 254Vac 254		Colour Red R Blue B Green G Amber A Yellow Y Clear C		Label None N Yes Y* *Please specify		Finish Natural black N Red R Blue B Yellow Y Grey G White W Special S* *Please specify	

General arrangement drawing (all dimensions in mm)

